

GATAS HEAVY DUTY



- 1 Alloy Steel Front Handle 2 Rise First Section 3 Rise Second Section
- 4 Solid Rubber Tires 5 Pipeline Neatly Arranged 6 Heightening Pad

Solid rubber packaging
Bass shock absorption and wear resistance



20T/50T (low-profile) suitable for buses, etc.




40T/80T suitable for small trucks, etc.



60T/120T suitable for heavy trucks, etc.



	Descripción	Unidad	50 Ton	80 Ton	120 Ton
/	Capacidad de carga	(t)	25/50	40/80	60/120
A	Altura mínima	(mm)	165	205	205
B	Altura de la primera sección	(mm)	90	97	87
C	Altura de la segunda sección	(mm)	75	90	80
D+E	Extensión de altura (Suplementos)	(mm)	35+60	35+60	35+60
F	Ancho	(mm)	290	300	330
G	Largo	(mm)	530	640	750
H	Altura del brazo / manija	(mm)	1130	1260	1260
I	Altura libre al suelo (Total)	(mm)	1340	1450	1500



Double handles at the front and back
Easy to move, safe and efficient
Ergonomic design



Pipelines are arranged in order
Pipelines are clearly protected by steel wires.
More stable and durable



Firm support plate
Durable and effective in protecting the cylinder
Prolong service life